

## OVERVIEW

Terraco Siltop is a premium quality exterior masonry paint based on silicone polymers which provide the coating with excellent dirt pick-up resistance and water repellence. Terraco Siltop has extremely high breathability which ensures enhanced long-life properties. Terraco Siltop has a matt finish and is available in a standard range of 50 colours.

## PRODUCT GRADES/CODES

White	61212
Pastel	61231
Mid	61232
Clear	61233

## PROPERTIES

Terraco Siltop is based on silane-siloxane polymers which provide the coating with the following unique properties:

- High water vapour transmission
- Excellent breathability
- Excellent dirt pick-up resistance
- Distinctive water beading effect
- Combined with specially graded filler, ensures film integrity over textured surfaces
- Excellent exterior durability
- Excellent coverage
- Low material consumption
- Mould resistant
- Extra long life

## AREA OF USE

TERRACO Siltop is used as an alternative to exterior masonry paint where high performance is required.

Terraco Siltop is used as a top coating system for textured surfaces to minimise the dirt pick-up problems normally associated with open pore textures.

## PREPARATION OF SURFACE

**New surfaces:** Ensure that all dust, dirt and foreign matter are scraped and brushed away. Also ensure the surfaces are free from salts, oil, grease and ridges. Protect all adjacent surfaces not to be covered. All cracks, chips, voids and damages should be repaired with Terraco Acrylic Filler.

**Old surfaces:** Before applying to old surfaces, ensure the substrate is firm. First wash down the surface with a sugar soap solution, rinse and allow to dry before repairing or applying the primer.

## PRIMING

Absorbent surfaces such as uncoated concrete and masonry should be primed with TERRACO Silprime. For previously painted surfaces P Primer should be used.

## APPLICATION & CLEANING OF TOOLS

When applying to old painted surfaces, first wash down with a soda/water solution, rinse and allow to dry before either patching or painting. Very porous substrates should be filled and may require a diluted first coat. Apply the paint by brush, roller or spray. The application should be continuous in order to avoid dry edges; therefore plan the application work accordingly. One or two coats is normally enough to give full coverage at a consumption rate of 0.3-0.4kg/m<sup>2</sup>.

Clean tools and equipment with water after use.

## HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

## PACKAGING AND STORAGE

Product is supplied in 5kg and 25kg plastic pails.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

**TECHNICAL DATA**

<b>Product</b>	Exterior silicone based emulsion paint.
<b>Binder</b>	Silane/siloxane.
<b>Pigments</b>	Lime and light-fast. Weather and pollution-resistant.
<b>Additives</b>	Bactericides, anti-corrosion, anti-foam agents, etc.
<b>Viscosity</b>	10,000cps
<b>Specific Weight</b>	55% by weight
<b>Solid Content</b>	55% ± 3%
<b>pH Value</b>	8-9
<b>Water Vapour Permeability (wet cup) sd. Value (m)</b>	0.04
<b>Liquid Water Transmission Rate W24-Value (kg/m<sup>2</sup>/h 0.5)</b>	0.06
<b>Adhesion Strength (N/mm<sup>2</sup>)</b>	2.7
<b>Silicone/Acrylic Ratio</b>	0.9:1.0
<b>Wet Scrubs</b>	>10,000
<b>Application Method</b>	Spray (airless or conventional), brush or roller.
<b>Material Consumption</b>	0.3-0.4kg/m <sup>2</sup>
<b>Finish</b>	Matt.
<b>Colours</b>	According to <i>TERRACO</i> colour charts. Any special colours can be matched on request.
<b>Packaging</b>	5kg and 25kg plastic pails.
<b>Storage</b>	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

**CHINA:**

Terraco Architectural Coatings China Co., Ltd.  
 Tel: +86 (0)20 8759 4742  
 Fax: +86 (0)20 8526 8056  
 E-mail: sales@terraco.com.cn  
 Web: www.terraco.com.cn

**Terraco Chemical (Shanghai) Co., Ltd.**

Tel: +86 (0)21 621020 48 / 18  
 Fax: +86 (0)21 625205 47  
 Email: sales@terraco.com.cn  
 Web: www.terraco.com.cn

**EGYPT:**
**Terraco Egypt Chemical Industries S.A.E.**

Tel: +20 (0)22 29184 53 / 57 / 58  
 Fax: +20 (0)22 29184 80  
 E-mail: terraco@terraco.com.eg  
 Web: www.terraco.com.eg

**JORDAN:**
**Jordan Swedish Polymers Industrial Corp.**

Tel: +962 (0)6 553 8751  
 Fax: +962 (0)6 553 6560  
 E-mail: terraco@nol.com.jo  
 Web: www.terraco.jo

**IRELAND:**
**Terraco Technical Centre, Ireland**

Tel: +353 (0) 404 66555  
 Fax: +353 (0) 404 66654  
 E-mail: technical-centre@terraco.com  
 Web: www.terraco.com

**PAKISTAN:**
**Terraco Pakistan Pvt. Ltd.**

Tel: +92 (0)42 3529 70 56-8  
 Fax: +92 (0)42 3529 70 55  
 Email: terraco@terraco.pk  
 Web: www.terraco.com

**ROMANIA:**
**Terraco Romania SRL**

Tel: +40 (0)749 203 133  
 Fax: +40 (0)318 148 810  
 E-mail: ahaque@terraco.com  
 Web: www.terraco.com

**RUSSIA:**
**OOO Terraco Sweden Ltd, Russia**

Tel: +7 (0)495 9212 237  
 Fax: +7 (0)495 6273 881  
 E-mail: adm@terraco.ru  
 Web: www.terraco.ru

**OOO Terraco Vostok Ltd**

Tel: +7 (0)4212 410563  
 Fax: +7 (0)4212 410591  
 E-mail: terracovostok@terracokhv.ru  
 Web: www.terraco.com

**SOUTH KOREA:**
**Terraco Korea Co., Ltd**

Tel: +82 (0) 2 5611 551  
 Fax: +82 (0)2 5671 771  
 E-mail: terraco@terraco.co.kr  
 Web: www.terraco.co.kr

**THAILAND:**
**Terraco Industry (Thailand) Limited**

Tel: +66 (0)2 946 68 56 / 58  
 Fax: +66 (0)2 946 68 59  
 E-mail: terraco@terraco.co.th  
 Web: www.terraco.com

**TURKEY:**
**Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS**

Tel: +90 (0)222 236 0423  
 Fax: +90 (0)222 236 0425  
 E-mail: terraco@terraco.com.tr  
 Web: www.terraco.com.tr

**UAE:**
**Terraco UAE Ltd**

Tel: +971 (0)4 326 2699  
 Fax: +971 (0)4 326 2733  
 E-mail: terraco@terraco.ae  
 Web: www.terraco.com

**UK:**
**ADDAGRIP**

Tel: +44 (0)1825 761 333  
 Fax: +44 (0)1825 768 566  
 E-mail: sales@addagrip.co.uk  
 Web: www.addagrip.co.uk / www.terraco.com

**VIETNAM:**
**Terraco Vietnam Co., Ltd**

Tel: +84 (0)650 3 820 100  
 Fax: +84 (0)650 3 820 101  
 E-mail: terraco@terraco.com.vn  
 Web: www.terraco.com

